



JiangSu Kintep Environmental Protection Equipment Co.,Ltd.

Website: www.kintep.net Tel: +86 523 89988802 Fax: +86 523 88638888
 Add: No.66 Wuliangsi Road, Sixiang Town, Medical High-tech Zone, Taizhou, Jiangsu, China

Specification

Equipment Name	Screw Press (SP) Sludge Dewatering Machine	
Picture		
Model	KTDL 252	
Dewatering Type	Screw Press	
Production Capacity (kg.dried sludge/hour)	30-60kg.DS/h	
Equipment Dimensions	L2810mm x W1120mm x H1600mm	
Net Weight	800kg	
Operation Weight	1320kg	
Power	1.47kw	
Inlet Flow-Sludge Content	3m ³ /h-10,000mg/L 1.2m ³ /h-50,000mg/L	
Mud Cake Moisture	Approx. 80%	
Working Hours	Automatically operating 24 hours per day	
Maintenance Frequency	10 min/day	
Specification	Item	Parameter
Material	Enclosure	304SS
	Screw Shaft	304SS
	Water Collection Shaft	304SS
	Flocculation Tank	304SS
	Spray System	304SS
	Solenoid Valve	304SS
	Liquid Level Switch	304SS



JiangSu Kintep Environmental Protection Equipment Co.,Ltd.

Website: www.kintep.net Tel: +86 523 89988802 Fax: +86 523 88638888
 Add: No.66 Wuliangsi Road, Sixiang Town, Medical High-tech Zone, Taizhou, Jiangsu, China

Specification

Screw Shaft	Diameter x Length	200mm dia x 1700mm
	Qty	2 piece
	Process	Fine machined, supersonic spray finish with reinforced blade
	Hardness	1100HV
Ring	Thickening Zone Rings	2.85±0.2mm (cold rolling)
	Dewatering Zone Rings	2.85±0.2mm (cold rolling)
	Washer	Thickening Zone: 3.30±0.2mm (fine machined) Dewatering Zone: 3.15±0.2mm (fine machined)
Water Collection Basin	Dimensions	1160mm x 880mm x 320mm
	Filtrate Discharge	DN125 flange (PN1.6MPa)
Flocculation Tank	Dimensions	570mm x 570mm x 850mm
	Qty	1 set
	Volume	0.28 m ³
	Stiring Device	1 set, 304SS
	Sludge Inlet	DN40 male NPT
	Overflow Nozzle	DN80 flange (PN1.6MPa)
	Chemical Injection Nozzle	DN15 male NPT
	Vent	DN50 female NPT
Enclosure	Dimensions	2360mm x 1100mm x 740mm
	Qty	1 set
Screw Drive	Power	0.55kw
	IP Grade	IP55
	Insulation Grade	F
	Rotating Speed	2.28-5.7rpm
	Reduction Ratio	246
	Qty	2 set
	Brand	TBA
Flocculator Motor	Power	0.37kw
	IP Grade	IP55
	Insulation Grade	F
	Rotating Speed	30rpm
	Reduction Ratio	48.17
	Qty	1 set
	Brand	TBA



JiangSu Kintep Environmental Protection Equipment Co.,Ltd.

Website: www.kintep.net Tel: +86 523 89988802 Fax: +86 523 88638888

Add: No.66 Wuliangsi Road, Sixiang Town, Medical High-tech Zone, Taizhou, Jiangsu, China

Specification

Spray System	Type	Cone water column
	Pressure	0.2MPa
	Water Consumption	116L/h
	Rinse Water Inlet Size	DN15 female NPT
	Spay Nozzle	16 pieces, 304SS
	Spray Pipe	DN15, 304SS
Solenoid Valve	Pipe Size	DN15
	Qty	1 set
	IP Grade	IP65
	Brand	TBA
Liquid Level Switch	Model	PS-3SC
	Size	60mm dia
	Brand	Omron
Electric Control Cabinet	Materials	Epoxy coated carbon steel
	Electrical Components	Schneider
	Frequency Converter	Schneider/Delta
	PLC	Siemens/VIPA

